



FLAMMABLE SOLVENT CLEANING SYSTEMS

- All stainless steel construction
- 14 gauge 316L stainless steel tank, 304 stainless steel skirt
- High performance ultrasonics, universa "U1B" transducers
- Powered by Neptune 40 kHz generator with sweep frequency
- Piezoelectric, metallurgically bonded transducers
- Thermostatically controlled heat Operating temperature: 32°F to 110°F
- regulated compressed air 25 p.s.i. @ 70 .f.m., cooling water 0.5 g.p.m.
- Over-temperature protection
- Fusible link safety cover
- Low purge pressure interlock
- Purge pressure delay-on
- Ultrasonic 30 minute timer
- Ultrasonic cycle start
- Purge system OK annunciator
- Low purge pressure annunciator
- Over temperature annunciator
- Pneumatic pump and filter
- Chiller option

HT-IPA - Series

All specifications are subject to change without notice

MODEL NUMBER	HT-1306-IPA	HT-2011-IPA
CAPACITY	3 GALLONS	11 GALLONS
TANK DIMENSIONS (L X W H)	13" x 6" x 10" (8"LL)	20" x 11" x 14" (12"LL)
UNIT DIMENSIONS (L X W H)	43" x 27" x 24"	43" x 27" x 24"
ULTRASONIC POWER	280W	840W

OPTIONS & ACCESSORIES: -

SS WIRE MESH BASKET

ELECTROPOLISHED TANK

SS PUMP & FILTER

Equipment has been approved for "Class I, Division I Group D, T4"

locations when properly installed according to the National Electric Code



RANSOHOFF BLACKSTONE-NEY ULTRASONICS CTG ASIA

Blackstone-NEY Ultrasonics

(800) 766-6606 P.O. Box 220 9 N. Main St. Jamestown, NY 14702-0220 www.ctgclean.com

Ransohoff

(800) 248-9274 4933 Provident Drive Cincinnati, OH 45246

CTG Asia

(86)0512-66161698 56 Songshan Road Suzhou New District Jiangsu Province, China PRC: 21515